## TILTED FACE TYPE DIAL TEST INDICATOR

- Meet DIN2270
- Jeweled bearing
- Carbide contact point
- Two measuring directions
- Anti magnetic body

7

- Supplied with two clamps: diameter Ø4mm and Ø8mm
- Optional accessory: styli (page 182)



2399-08


Code	Range	Graduation	Accuracy	Hysteresis	Dial reading
2399-08*	0.8mm	0.01mm	13µm	3µm	0-40-0


Supplied with manufacturer inspection certificate traceable to NIST USA



**JEWELED BEARING** 







TRACEABLE TO NIST


## LONG STYLUS DIAL TEST INDICATOR



- Two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter Ø4mm and Ø8mm
- Optional accessory: styli (page 182)




2383-08A




clamp (included)

Unit: mm



Code 2383-08A\* 0.8mm 0.01mm 13µm 3µm

## LARGE RANGE DIAL TEST INDICATOR




- Dial reading: 0-40-0
- Jeweled bearing
- Carbide contact point ■ Two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter Ø4mm and Ø8mm
- Optional accessory: styli (page 182)

Code	Range	Graduation	Accuracy	Hvsteresis
2386-16A*	_		25µm	8µm

 $<sup>^{</sup>ullet}$ Supplied with manufacturer inspection certificate traceable to NIST USA







2386-16A

Supplied with manufacturer inspection certificate traceable to NIST USA