SUITABLE FOR JEWELLERY

Lie-down use for small articles on the table

back

measuring tips

two measuring tips are flush with the back

THICKNESS GAGE

Unit: mm

Ø40

80

Ø10

14

48

8

2361-10

Code	Range	Graduation	Accuracy
2361-10	0-10mm	0.1mm	±0.05mm

THICKNESS GAGE

Unit: mm

67

Ø43

Ø6

10

2363-10

■ Stainless steel spindle tip and anvil

Code	Range	Graduation	Accuracy
2363-10	0-10mm	0.01mm	±0.03mm

THICKNESS GAGES

Unit: mm

Ø50

L

L1

2862-101

Code	Range	Graduation	Accuracy	L	L1
2862-101	0-10mm	0.05mm	±0.1mm	35mm	85mm
2862-102	0-10mm	0.05mm	±0.1mm	60mm	110mm

THICKNESS GAGE

Unit: mm

Ø50

35

87

2863-10

Code	Range	Graduation	Accuracy
2863-10	0-10mm	0.05mm	±0.1mm

THICKNESS GAGE WITH POINTED TIPS

Unit: mm

Ø50

35

85

2866-10

■ Pointed tips fit into small grooves and recesses

Code	Range	Graduation	Accuracy
2866-10	0-10mm	0.05mm	±0.1mm

8

https://precishop.hu