-INSIZE-

RELATIVE PRODUCT: CRIMP HEIGHT MICROMETER (CODE 3266-25BA, 3566-25BA)

DATA OUTPUT

- Measure crimp height
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, meet DIN862
- Made of stainless steel

With data interface (data output cable code 7315-21, 7302-21, optional)

Code	Range	Accuracy				
1165-150A	0-150mm/0-6"	±0.03mm				

Built-in wireless


(receiver code 7315-2/3/6/7/8 is required)

Code	Range	Accuracy			
1165-150AWL	0-150mm/0-6"	±0.03mm			

DIGITAL CRIMP HEIGHT CALIPERS







DATA **OUTPUT**

■ Measure diameter of wire ropes, and thickness of soft materials like rubber, sponge, etc.

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel

With data interface (data output cable code 7315-21, 7302-21, optional)

Code	Range	Accuracy
1172-200	0-200mm/0-8"	±0.07mm


Built-in wireless


(receiver code 7315-2/3/6/7/8 is required)

Code	Range	Accuracy
1172-200WL	0-200mm/0-8"	±0.07mm


DIGITAL CALIPERS WITH LARGE MEASURING FACES







(mm)



DATA OUTPUT

■ Measure thickness of soft sheets

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel

DIGITAL CALIPERS WITH DISK FACES



With data inte	rface							
Code	Range	Accuracy	L	а	b	С	Ød	Data out
1533-150	0-150mm/0-6"	±0.04mm	245	50	11	16	20	73

Code	Range	Accuracy	L	а	b	С	Ød	Data output cable (optional)
1533-150	0-150mm/0-6"	±0.04mm	245	50	11	16	20	7315-21, 7302-21
1533-200	0-200mm/0-8"	±0.05mm	310	80	11	16	30	7315-21, 7302-21
1533-500	0-500mm/0-20"	±0.07mm	680	150	20	24	50	7315-22, 7302-22
Built-in wirele	ss (receiver code							

Built-in wireless (receiver code 7315-2/3/6/7/8 is required)									
Code	Range	Accuracy	L	а	b	С	Ød		
1533-150WL	0-150mm/0-6"	±0.04mm	245	50	11	16	20		
1533-200WL	0-200mm/0-8"	±0.05mm	310	80	11	16	30		
1533-500WL	0-500mm/0-20"	±0.07mm	680	150	20	24	50		

