



Refractive index measurement for laboratories and the industry

Features

- The KERN ORA refractometers are universal, maintenance-free analogue handheld refractometers
- The handy and robust design allows the easy, efficient and sustainable use in everyday life
- Manually calculated conversions and errors of the user are avoided by multiple selectable scales
- These scales are especially developed, exactly calculated and checked. They are also characterized by their thin and clear lines
- The optical system and the prism cover are made of special material which allows a low-tolerance measuring
- All ORA models are equipped with an eyepiece for easy and smooth setting for many different diopter strengths

- The models marked with "ATC" have an automatic temperature compensation which enables accurate measurement at different ambient temperatures (10 °C/30 °C)
- The following accessory-parts are included:
 - Storage box
 - Calibration liquid
 - Calibration block (if required)
 - Pipette
 - Screwdriver
 - Cleaning tissue
- Further accessories are optionally available

Technical data

- Die-cast housing of copper-aluminium alloy, chrome coated
- Measurement temperature without ATC: 20 °C
- Measurement temperature range with ATC: 10 °C/30 °C
- Dimensions of the box: 205×75×55 mm (depending on the model)
- Product length: approx. 130 – 200 mm (depending on the model)
- Net weight approx. 135 – 600 g (depending on the model)

Note: Also available with calibration certificate, see page 106

STANDARD



1 DAY

OPTION



AUTO
ATC

Scope of application: Industry/Automotive

The following models are particularly suitable for the measurement and determination of AdBlue®, glycol concentration ethylene (EG) and propylene (PG), battery fluid (BF), urea, the freezing point of windscreen wash water (CW). Furthermore these models are suitable for the measurement of thermal exchange systems.

The main scope of applications is:

- Automotive industry: Car-workshops and producers, in accordance with the VW standards G11/G12 and G13
- Chemical industry
- Solar industry: Antifreeze monitoring



Model	Scales	Measuring range	Division	ATC
KERN				
ORA 4FB*	Ethylene glycol (G11/12)	-50 - 0 °C	1 °C	
	Propylene glycol (G13)	-50 - 0 °C	1 °C	
	Windshield washer fluid	-40 - 0 °C	5 °C	
	Battery fluid	1,10 - 1,40 kg/l	0,01 kg/l	
ORA 4FA	Ethylene glycol (G11/12)	-50 - 0 °C	1 °C	
	Propylene glycol (G13)	-50 - 0 °C	1 °C	
	Windshield washer fluid	-40 - 0 °C	5 °C	✓
	Battery fluid	1,10 - 1,40 kg/l	0,01 kg/l	
ORA 1UB*	Urea	0 - 40 %	0,2 %	
ORA 1UA	Urea	0 - 40 %	0,2 %	✓
ORA 4UB*	Urea	30 - 35 %	0,2 %	
	Ethylene glycol (G11/12)	-50 - 0 °C	1 °C	
	Propylene glycol (G13)	-50 - 0 °C	1 °C	
	Windshield washer fluid	-40 - 0 °C	5 °C	
ORA 4UA	Battery fluid	1,10 - 1,40 kg/l	0,01 kg/l	
	Urea	30 - 35 %	0,2 %	
	Ethylene glycol (G11/12)	-50 - 0 °C	1 °C	
	Propylene glycol (G13)	-50 - 0 °C	1 °C	✓
	Windshield washer fluid	-40 - 0 °C	5 °C	
	Battery fluid	1,10 - 1,40 kg/l	0,01 kg/l	

! * ONLY WHILE STOCKS LAST

Accessory parts: Analogue refractometer – ORA



Prism coverplate with LED ORA-A1101



Calibration liquid/Contact liquid



Leather bag ORA-A2103



Calibration block

Model	Description
KERN	
ORA-A1101	Prism coverplate with integrated LED illumination
ORA-A2103	Leather bag for analog refractometers
ORA-A2107	Leather bag for Gem refractometers (Spare part)
ORA-A1010	Calibration liquid – distilled water – Set of 5 Volume: 5× approx. 3 ml
ORA-A1002	Contact liquid – Clove oil (for Calibration value 19,6%) Volume: approx. 2 ml
ORA-A1003	Calibration liquid – saturated salt solution Volume: approx. 2 ml
ORA-A1004	Contact liquid – Clove oil (for Calibration value 78,8%) Volume: approx. 2 ml
ORA-A1005	Calibration block for models ORA 82BB, ORA 3HA, ORA 3HB, ORA 6HA, ORA 6HB, ORA 4RR
ORA-A1007	Contact liquid – Diiodomethane “Standard” (Refractive index: 1,74 nD) Volume: approx. 2 ml
ORA-A3001	Contact liquid – Diiodomethane “Pro” (Refractive index: 1,79 nD) Volume: approx. 2 ml
ORA-A1008	Calibration block for model ORA 1GG
ORA-A2001	Prism coverplate (spare part)

Relationship overview – refractometer calibration (analogue)

Model refractometer	Calibration value	Calibration liquid	Article number liquid	Calibration block	Article number calibration block
ORA 10BA; ORA 10BB; ORA 18BB; ORA 1WA; ORA 1WB; ORA 20BA; ORA 20BB; ORA 32BA; ORA 32BB; ORA 3SA; ORA 3SB; ORA 3WA; ORA 3WB; ORA 7WA; ORA 80BB; ORA 80BE; ORA 3AB; ORA 3AA	0 % Brix	distilled water	ORA-A1010	-	-
ORA 4AA; ORA 4AB	0 ° Plato	distilled water		-	
ORA 1UA; ORA 1UB	0 % Urea	distilled water		-	
ORA 4FA; ORA 4FB; ORA 4UA; ORA 4UB	0 °C EG/PG/CW	distilled water		-	
ORA 1SA; ORA 1SB	0 ‰ Salinity	distilled water	ORA-A1010	-	-
ORA 2SA; ORA 2SB	0 % Salt (NaCl)	distilled water		-	
ORA 2AB	0 % Vol (weight)	distilled water		-	
ORA 2PA; ORA 2PB; ORA 5PB	1,000 sg Urine	distilled water		-	
ORA 62BA; ORA 62BB	29,6 % Brix	saturated salt solution	ORA-A1003	-	-
ORA 3HA; ORA 3HB; ORA 82BB	78,8 % Brix	Clove oil CAS 8000-34-8	ORA-A1004	yes	ORA-A1005
ORA 4RR	1,4875 nD	Clove oil CAS 8000-34-8	ORA-A1004	yes	ORA-A1005
ORA 6HA; ORA 6HB	19,6 % Water content	Clove oil CAS 8000-34-8	ORA-A1002	yes	ORA-A1005
ORA 1GG	1,515 nD	Diiodomethane CAS 90-11-9	ORA-A1007	yes	ORA-A1008