


Dial indicator with range 30 mm or 50 mm

- zur Messung von großen Längen und Längendifferenzen
- Zentralzeiger für 1/100 mm Ablesung,
- Außenring zur Nulleinstellung drehbar
- Klemmschraube zur Fixierung des Außenringes
- Messuhr im Metallgehäuse, mattverchromt
- Einspannschaft 8 h6, gehärtet und geschliffen
- Messeinsatz auswechselbar M 2,5
- Genauigkeit nach Werksnorm
- Lieferung im Kasten

- measurement of long lengths and length differences
- central pointer for 1/100 mm reading
- scale rotatable by outer ring
- with set screw
- with metal case, matt chrome-plated
- clamping shank 8 h6, hardened and ground
- exchangeable insert M 2.5
- accuracy according to works standard
- in a box



konzentrische Millimeteranzeige, mit zwei verstellbaren Toleranzmarken/ extra scale for 1 mm reading, with two adjustable tolerance marks



Bestell-Nr. Order-No.	Messbereich Range mm	Ablesung Reading mm	Genauigkeit Accuracy µm	Ø C mm	A mm	F mm	G mm	H mm	Euro/St. Euro/Pc.
01024005	30	0,01	34	58	122	18	33	53,5	73,00
01024007	50	0,01	55	60	261	58	60	55,0	125,00
01024006	50	0,01	55	76	177	34	58,5	70,0	170,00

Doppel-Messuhr beidseitig ablesbar

Double dial indicator reading front and back side

- mit beidseitiger Anzeige für Messungen bei z.B. eingeschränktem Sichtfeld
- Zentralzeiger für 1/100 mm Ablesung, kleiner Zeiger für 1 mm Ablesung
- Außenring zur Nulleinstellung drehbar
- Messuhr im Metallgehäuse, mattverchromt
- Einspannschaft 8 h6, gehärtet und geschliffen
- Messeinsatz auswechselbar M 2,5
- Genauigkeit nach Werksnorm
- Lieferung im Kasten

- Double dial indicator
- central pointer for 1/100 mm reading, extra scale for 1 mm reading
- scale rotatable by outer ring
- with metal case, matt chrome-plated
- clamping shank 8 h6, hardened and ground
- exchangeable insert M 2.5
- accuracy according to works standard
- in a box



Bestell-Nr. Order-No.	Messbereich Range mm	Ablesung Reading mm	Genauigkeit Accuracy µm	Ø C mm	A mm	F mm	G mm	H mm	Euro/St. Euro/Pc.
01023008	10	0,01	17	58	110	18	20,5	53,5	130,00