



INDUSTRIAL TORQUE WRENCHES ADJUSTABLE & 'P' TYPE - NEW GENERATION



A long-time customer favourite for their unmistakable signal and robustness but now simple to accurately set and split for ease of storage and transportation.

- Unique profiled cam and reaction plate - gives clear torque break point reducing the possibility of over-torquing
- Robust construction gives accurate results to  $\pm 4\%$  even in arduous working conditions, meeting the requirements of ISO 6789-1:2017
- Easy to read scale is shielded from dust, dirt and spray
- Easy to set accurately
- Can be split and packed in two parts for a smaller, easier to transport package
- Push-through ratchet allows two direction torquing (Not available for 6R-N models)
- Designed to be cost effectively serviced
- New handle - more comfortable and guides operator's hand to correct position



2	RATCHET ADJUSTABLE - DUAL SCALE
120101	3AR-N, 3/4", 120 - 600 N·m, 100 - 450 lbf-ft
120101.01	3AR-N, 1", 120 - 600 N·m, 100 - 450 lbf-ft
120110	4AR-N, 3/4", 200 - 800 N·m, 150 - 600 lbf-ft
120110.01	4AR-N, 1", 200 - 800 N·m, 150 - 600 lbf-ft
120115	5R-N, 3/4", 300 - 1,000 N·m, 200 - 750 lbf-ft
120115.01	5R-N, 1", 300 - 1,000 N·m, 200 - 750 lbf-ft
120118	5AR-N, 3/4", 700 - 1,500 N·m, 500 - 1,000 lbf-ft
120118.01	5AR-N, 1", 700 - 1,500 N·m, 500 - 1,000 lbf-ft
120120	6R-N, 1", 900 - 2,000 N·m, 700 - 1,500 lbf-ft

2	RATCHET ADJUSTABLE - N·m ONLY
120107	3AR-N, 3/4", 120 - 600 N·m
120107.01	3AR-N, 1", 120 - 600 N·m
120114	4AR-N, 3/4", 200 - 800 N·m
120114.01	4AR-N, 1", 200 - 800 N·m
120117	5R-N, 3/4", 300 - 1,000 N·m
120117.01	5R-N, 1", 300 - 1,000 N·m
120119	5AR-N, 3/4", 700 - 1,500 N·m
120119.01	5AR-N, 1", 700 - 1,500 N·m
120121	6R-N, 1", 900 - 2,000 N·m

2	TORQUE HANDLE ADJUSTABLE - DUAL SCALE
120102	3AR-N, 22 mm spigot, 120 - 600 N·m, 100 - 450 lbf-ft

2	TORQUE HANDLE ADJUSTABLE - N·m ONLY
120108	3AR-N, 22 mm spigot, 120 - 600 N·m



2	RATCHET PRODUCTION 'P' TYPE (Must be set using a Torque Tester, see pages 81-88)
120104	3AR-N, 3/4", 120 - 600 N·m, 100 - 450 lbf-ft
120104.01	3AR-N, 1", 120 - 600 N·m, 100 - 450 lbf-ft
120111	4AR-N, 3/4", 200 - 800 N·m, 150 - 600 lbf-ft
120111.01	4AR-N, 1", 200 - 800 N·m, 150 - 600 lbf-ft
120116	5R-N, 3/4", 300 - 1,000 N·m, 200 - 750 lbf-ft
120116.01	5R-N, 1", 300 - 1,000 N·m, 200 - 750 lbf-ft
120130	5AR-N, 3/4", 700 - 1,500 N·m, 500 - 1,000 lbf-ft
120130.01	5AR-N, 1", 700 - 1,500 N·m, 500 - 1,000 lbf-ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)

2	TORQUE HANDLE PRODUCTION 'P' TYPE (Must be set using a Torque Tester, see pages 81-88)
120105	3AR-N, 22 mm spigot, 120 - 600 N·m, 100 - 450 lbf-ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)